AMENDMENTS TO THE CLAIMS

This listing of claims will replace all prior versions and listings of claims in the application:

LISTING OF CLAIMS:

- 1. (original): A method for producing a particulate alumina, comprising heat-treating (calcining) a composition comprising alumina, an alumina hydrate, ammonium chloride and a halogen compound other than ammonium chloride and then disintegrating the heat-treated product.
- 2. (original): The production method of a particulate alumina as claimed in claim 1, wherein the halogen compound other than ammonium chloride is a fluorine compound or a boron-fluorine compound.
- 3. (original): The production method of a particulate alumina as claimed in claim 2, wherein the fluorine compound is at least one member selected from the group consisting of AlF₃, NaF, CaF₂, MgF₂ and Na₃AlF₆.
- 4. (original): A method for producing a particulate alumina, comprising heat-treating (calcining) a composition comprising alumina, an alumina hydrate, ammonium chloride and a boron compound and then disintegrating the heat-treated product.

2

- 5. (original): A method for producing a particulate alumina, comprising heat-treating (calcining) a composition comprising alumina, an alumina hydrate, ammonium chloride, a halogen compound other than ammonium chloride, and a boron compound then disintegrating the heat-treated product.
- 6. (currently amended): The production method of a particulate alumina as claimed in claim 4 or 5, wherein the boron compound is at least one member selected from the group consisting of B₂O₃, H₃BO₃, mNa₂O·nB₂O₃ (m and n each represents an integer of 1 or more, hereinafter the same) and a boron-fluorine compound.
- 7. (currently amended): The production method of a particulate alumina as claimed in <u>claim 1 any</u> one of claims 1 to 6, wherein the particulate alumina has a rounded shape having no cutting edge.
- 8. (currently amended): The production method of a particulate alumina as claimed in <u>claim 1</u> any one of claims 1 to 7, wherein the composition is previously granulated before heat-treating (calcining) the composition.
- 9. (currently amended): The production method of a particulate alumina as claimed in <u>claim 1</u> any one of claims 1 to 8, wherein the alumina hydrate is at least one member selected from the group

consisting of an aluminum hydroxide, an alumina gel and a partially hydrated aluminum compound.

- 10. (currently amended): The production method of a particulate alumina as claimed in <u>claim</u>

 <u>lany one of claims 1 to 9</u>, wherein the average particle size of the particulate alumina is 10 μm or less.
- 11. (original): The production method of a particulate alumina as claimed in claim 10, wherein the average particle size of the particulate alumina is from 0.3 to $8 \mu m$.
- 12. (currently amended): A resin composition comprising a particulate alumina produced by the production method as claimed in <u>claim 1 any one of claims 1 to 11</u>, and a polymer compound.
- 13. (original): The resin composition as claimed in claim 12, wherein the polymer compound is at least one member selected from an aliphatic resin, an unsaturated polyester resin, an acrylic resin, a methacrylic resin, a vinyl ester resin, an epoxy resin and a silicone resin.
- 14. (currently amended): The resin composition as claimed in claim 12-or 13, wherein the content of the particulate alumina is 70 mass% of more.

- 15. (currently amended): The resin composition as claimed in <u>claim 12</u> any one of claims 12 to 14, wherein the particulate alumina is coated with a surface-treating agent.
- 16. (original): The resin composition as claimed in claim 15, wherein the surface-treating agent is a silane coupling agent.
- 17. (original): The resin composition as claimed in claim 15, wherein the surface-treating agent is a compound having any one or more group selected from the group consisting of an amino group, a carboxyl group and an epoxy group.
- 18. (original): The resin composition as claimed in claim 15, wherein the surface-treating agent is a modified silicone oil.
- 19. (currently amended): The resin composition as claimed in <u>claim 15</u> any one of claims 15 to 18, wherein the coverage of the surface-treating agent is from 0.05 to 5 mass% based on the particulate alumina.
- 20. (currently amended): A ceramic composition comprising a particulate alumina produced by the production method as claimed in claim 1 any one of claims 1 to 11.

Preliminary Amendment National Stage of PCT/JP2004/008546

- 21. (currently amended): An electronic component or semiconductor device comprising the resin composition as claimed in <u>claim 12</u> any one of claims 12 to 19.
- 22. (currently amended): A CPU or PDP comprising the resin composition as claimed in <u>claim</u>

 12any one of claims 12 to 19.
- 23. (currently amended): A peripheral equipment for batteries, or a peltier element, an inverter or a power transistor, comprising the resin composition as claimed in <u>claim 12</u> any one of claims 12 to 19.